

Item no.: 222-415
 Product description: COMPACT CONNECTOR 5-CONDUCTOR TERMINAL BLOCK WITH LEVERS MAX. CONTINUOUS USAGE TEMPERATURE 85 °C



Produkt kann von Bild abweichen / product may differ

Packing unit 400 10*40 pieces

RoHS compliant

Product group	7 (Push Wire Conn.)
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 14 AWG
Wiring method	e+f
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Wiring method	f
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	32 A
Measured voltage EN	600 V
Current intensity EN	20 A
Weight	6.6 g
Color	gray
Wiring type	Side-entry
No. of connection Points	5

No. of potentials	1
Height	14.5 mm
Height	0.571 in
Width	26.6 mm



Width	1.047 in
Depth	20.5 mm
Depth	0.807 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Customs Tariff No.	85369010
Country of Origin	Deutschland



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
222-415	ABS	10-HN17750340X	450	32	0,5-4
222-415	cULus listed	E69654	600	20	28-12
222-415	ENEC15	DK140137-01	450	32	0,5-4
222-415	PSE	JET0695-43040-1003	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected