



GE
Lighting

71444 - GEC226-MVPS-SE

GE CFL Multi-Volt ProLine™ Electronic Program / Rapid Start Ballast

- Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- Programmed starting for extended lamp life
- End-of-Lamp-Life Protection
- Color Coded Poke-In Connectors simplifies wiring
- Dual-Entry Connectors accessible from bottom or side

GENERAL CHARACTERISTICS

Application	2-CFQ26W, FT24 or 1-42W, CFTR32 Side Exit 120-277V Proline PS
Category	Compact Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Series
Line Voltage Regulation (+/-)	10.0 %
Ambient Temperature (MAX)	40.0 °C (4 °C)
Case Temperature (MAX)	75.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Auto-restart / Thermally protected / Universal voltage

PRODUCT INFORMATION

Product Code	71444
Description	GEC226-MVPS-SE
Standard Package	Case
Standard Package GTIN	10043168714447
Standard Package Quantity	10
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168714440

DIMENSIONS

Case dimensions	
Length (L)	5.0 in(127.00 mm)
Width (W)	2.4 in(60.96 mm)
Height (H)	1.0 in(25.40 mm)
Mounting dimensions	
Bracket Length (BL)	NaN in(NaN mm)
Mount Length (M)	4.6 in(117.60 mm)
Mount Width (X or F)	NaN in(NaN mm)
Mount Slots (MS)	NaN in(NaN mm)
Weight	0.57 lb
Exit Type	Poke-in
Remote Mounting Distance	12.0 ft
Remote Mounting Wire Gauge	18.0 AWG

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50.0 Hz / 60.0 Hz
--------------------------	-------------------

SAFETY & PERFORMANCE

- CSA
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type CC
- UL Type HL
- FCC Part 18 Class B at 120 volts

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (°F/°C)
FT24W/4P	2	120	48	0.41 A	0.93	1.94	99	1.5	10.0	-20.0 °F / NaN
FT24W/4P	2	277	48	0.18 A	0.93	1.94	99	1.5	10.0	-20.0 °F / NaN
FC16T9/40W	1	120	43	0.16 A	1.00	2.33	97	1.5	10.0	-20.0 °F / NaN
FC16T9/40W	1	277	43	0.16 A	1.00	2.33	97	1.5	10.0	-20.0 °F / NaN
FC16T9	1	120	43	0.16 A	1.00	2.33	97	1.5	10.0	-20.0 °F / NaN
FC16T9	1	277	43	0.16 A	1.00	2.33	97	1.5	10.0	-20.0 °F / NaN
F24T5/HO	2	120	51	0.44 A	1.00	1.96	99	1.5	10.0	-20.0 °F / NaN

F24T5/HO	2	277	51	0.19 A	1.00	1.96	98	1.5	10.0	-20.0 °F / NaN
CFTR42W/4P	1	120	46	0.38 A	0.98	2.13	98	1.5	10.0	-20.0 °F / NaN
CFTR42W/4P	1	277	46	0.17 A	0.98	2.13	98	1.5	10.0	-20.0 °F / NaN
CFTR32W/4P	1	120	36	0.31 A	0.98	2.72	98	1.5	10.0	-20.0 °F / NaN
CFTR32W/4P	1	277	36	0.13 A	0.98	2.72	98	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	1	120	29	0.24 A	1.10	3.79	98	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	1	277	29	0.11 A	1.10	3.79	98	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	2	120	54	0.45 A	1.00	1.85	99	1.5	10.0	-20.0 °F / NaN
CFTR26W/4P	2	277	54	0.2 A	1.00	1.85	99	1.5	10.0	-20.0 °F / NaN
CFS21W/4P	2	120	51	0.42 A	1.12	2.20	99	1.5	10.0	-20.0 °F / NaN
CFS21W/4P	2	277	51	0.18 A	1.12	2.20	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	1	120	27	0.23 A	1.00	3.70	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	1	277	27	0.1 A	1.00	3.70	99	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	2	120	51	0.43 A	1.00	1.96	98	1.5	10.0	-20.0 °F / NaN
CFQ26W/4P	2	277	51	0.19 A	1.00	1.96	98	1.5	10.0	-20.0 °F / NaN

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.