


Item no.: 773-118
 Product description: PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 8-CONDUCTOR TERMINAL BLOCK



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	7 (Push Wire Conn.)
pole count	8
Cross section [mm ²]	0.75 - 2.5 mm ²
Cross section [AWG]	18 - 12 AWG
Wiring method	e
Connection method	PUSH WIRE®
Cross section [mm ²]	1.5 - 2.5 mm ²
Cross section [AWG]	16 - 12 AWG
Wiring method	st
Connection method	PUSH WIRE®
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	24 A
Weight	5 g
Color	green
No. of connection Points	8
No. of potentials	1
Height	13.1 mm

Height
Width
Width

0.516 in
24 mm
0.945 in



Depth	19.5 mm
Depth	0.768 in
Strip length from	12 mm
Strip length to	12 mm
Strip length	0.47 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
773-118	ABS	10-HN17750340X	400	24	0,75-2,5
773-118	BV	11941/BO	300	24	2,5
773-118	CCA	DK2520	400	24	0,75-2,5
773-118	CSA	154112-1059435	600	20	12-18
773-118	FIMKO	FI14401	400	24	0,75-2,5
773-118	GL	17294-00HH	400	24	0,75-2,5
773-118	LR	04/20013(E3)	400	24	0,75-2,5
773-118	NEMKO	P99102807	400	24	0,75-2,5
773-118	RMR	11130002	400	24	0,75-2,5
773-118	SEMKO	9951003/01	400	24	0,75-2,5
773-118	UL listed	E201573			12-18
773-118	UL listed	E69654	600	20	12-18

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected