


Item no.: 773-166  
 Product description: PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 6-CONDUCTOR TERMINAL BLOCK



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	7 (Push Wire Conn.)
pole count	6
Cross section [mm <sup>2</sup> ]	0.75 - 2.5 mm <sup>2</sup>
Cross section [AWG]	18 - 12 AWG
Wiring method	e
Connection method	PUSH WIRE®
Cross section [mm <sup>2</sup> ]	1.5 - 2.5 mm <sup>2</sup>
Cross section [AWG]	16 - 12 AWG
Wiring method	st
Connection method	PUSH WIRE®
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	24 A
Weight	4.25 g
Color	violet
No. of connection Points	6
No. of potentials	1
Height	13.1 mm

Height  
Width  
Width

0.516 in  
18.8 mm  
0.74 in



Depth	19.5 mm
Depth	0.768 in
Strip length from	12 mm
Strip length to	12 mm
Strip length	0.47 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
773-166	CSA	154112-1059435	600	20	12-18
773-166	UL listed	E69654	600	20	12-18

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected