

---

Item no.: 873-902  
Product description: 2 POLE

---



Produkt kann von Bild abweichen / product may differ

### RoHS compliant

Weight	4.736 g
No. of connection Points	4
No. of potentials	2
pole count	2
Cross section [mm <sup>2</sup> ]	0.75 - 4 mm <sup>2</sup>
Cross section [AWG]	18 - 12 AWG
Cross section to [mm <sup>2</sup> ]	0.75 mm <sup>2</sup>
Cross section to [AWG]	18 AWG
Height	13.2 mm
Height	0.52 in
Width	13 mm
Width	0.512 in
Depth	42 mm
Depth	1.654 in
Strip length from	11 mm
Strip length to	13 mm
Strip length	0.47 in
Strip length from	9 mm
Strip length to	11 mm

Strip length	0.39 in
Cross section [mm <sup>2</sup> ]	1.5 - 4 mm <sup>2</sup>
Cross section [AWG]	16 - 12 AWG



Wiring method	e
Connection method	PUSH WIRE®
Wiring method	m
Customs Tariff No.	85369010
Country of Origin	China



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
873-902	CCA	NL6389	400	6	0,75-4
873-902	CSA	154112-1961671	600	6	18
873-902	cULus listed	E313353	600	6	18
873-902	KEMA	2119255.01	240	6	0,75-4

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected