


# WPLED10/PC

10 Watt Surface mount or Junction Box LED Wallpack. Equivalent to 70W HPS. IESNA Full Cutoff, Fully Shielded optics. Mount at 7-10'. 5 year warranty.

Color: Bronze

Weight: 3.3 lbs



## LED Info

Watts: 10W  
 Color Temp: 5000K (Cool)  
 Color Accuracy: 92  
 L70 Lifespan: 100000  
 LM79 Lumens: 547  
 Efficacy: 41 LPW

## Driver Info

Type: Constant Current  
 120V: 0.21 A  
 208V: 0.14 A  
 240V: 0.12 A  
 277V: N/A  
 Input Watts: 13W  
 Efficiency: 76%

## Technical Specifications

### UL Listing:

Suitable for Wet Locations as a Downlight. Suitable for Damp Locations as an Uplight. Wall Mount only. Suitable for Mounting within 4ft. of ground.

### Lumen Maintenance:

The LED will deliver 70% of its initial lumens at 100,000 hours of operation.

### Finish:

Chip and fade resistant polyester powder coat finish.

### Color Stability:

RAB LEDs exceed industry standards for chromatic stability.

### Color Uniformity:

RAB's range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

### Cold Weather Starting:

The minimum starting temperature is -40°F/-40°C

### Photocell:

Button Photocell installed and wired for 120V

### Ambient Temperature:

Suitable for use in 40°C (104°F) ambient temperatures

### Fixture Efficacy:

41 Lumens per Watt

### Color Accuracy:

92 CRI

### Color Temperature (Nominal CCT):

5000K

### Driver:

Multi-chip 10W high output long life LED Driver Constant Current, Class II, 120V-240V, 50/60 Hz, 350mA

### Thermal Management:

Cast aluminum Thermal Management system for optimal heat sinking. The LPACK is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

### Housing:

Precision die cast aluminum housing, lens frame.

### Mounting:

Junction box.

### California Title 24:

LPACK complies with California Title 24 building and electrical codes.

### Green Technology:

RAB LEDs are Mercury, Arsenic and UV free.

### Patents:

The LPACK design is protected under patents pending in the U.S., Canada, China, Taiwan and Mexico.

### Dark Sky Approved:

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

### For use on LEED Buildings:

IDA Dark Sky Approval means that this fixture can be used to achieve LEED Credits for Light Pollution Reduction.

**IESNA LM-79 & IESNA LM-80 Testing:**

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

**Gaskets:**

High Temperature Silicone

**Warranty:**

RAB LED fixtures give you peace of mind because both the fixture and driver components are backed by RAB's 5 Year Warranty. For more information,

**Equivalency:**

The WPLED10 is Equivalent in delivered lumens to a 70W Metal Halide Wallpack.

**HID Replacement Range:**

The WPLED10 can be used to replace 35-100W Metal Halide Wallpacks based on delivered lumens.

**Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

**Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010)

**Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

**GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4